MANHATTAN

The Beton effect, the star's material of « trendy » walls

Imagine and realize all your decoration's desires with the beton's effect coating : you can realize minimalist or audacious decors according to your creativeness and make silky and colored surfaces with a purified elegance.



Our products were studied to simplify their implementation, for their differents aspects and for their ecological quality.

Art avenue INTERIOR WALL DECORATION fashion your wall



For sale by :

08 2000 66 22 www.740artavenue.fr

Also exist in the range deco 740 Art avenue:







Art avenue INTERIOR WALL DECORATION

MANHATTAN Beton effect



www.740artavenue.fr

MANHATTAN BETON EFFECT

Create a sophisticated and contemporary atmosphere with **MANHATTAN**, thin cover material which gives to your walls the silky aspect of a matt or polished beton : rough, shod, studded, structured, brushed shod...



Colour chart 740 Art avenue

Beaches			
	Bora Bora	Recife	Avalon
Spices			
001000			
	Ceylan	Java	Bali
Islands			
	Motu	Kami	Victoria
Forests			
FOIESIS			
	Ituri	Sichuan	Bwindi
Gardens			
	Haleone	Alhambra	Adelaïde
Diver	Haleone	Alhambra	Adelaïde
Rivers	Haleone	Alhambra	Adelaïde
Rivers	Haleone	Alhambra	
Rivers	Haleone	Alhambra Tamise	Adelaïde
Rivers Hang gliders			

In spite of the care we took of this document, we can not guarantee to match the real colours.

PREPARATION :

Walls have to be clean, healthy, dry, non greasy, cohesive, devoid of any crisp parts. They have to follow DTU 59.1 recomandation. In case of plates of plaster or fillers plaster or plaster and lime, apply beforehand a coat of 740 Imprim.

MIXING AND PIGMENTATION :

Mix beforehand the necessary pigments with a part of **MANHATTAN** binder, until obtening homogeneous mixture. Then mix **MANHATTAN** powder with binder until obtening homogeneous dough. The time of use is approximately 2 hours in 20°C.

MPLEMENTATION :

Apply MANHATTAN with the help of a lisseuse in two or three coats according to the expected results. Protect it by applying a finition wax. Cleaning of tools in the water.

LES EFFETS :

Rough : apply a first coat of 1 mm in thickness, shod when the product begin to dry, add a second coat by structuring the aspect, shod again from the beginning of the drying.

Shod : apply a first coat of 0.5 mm in thickness with the help of the lisseuse, shod and add a second coat by slicking the material, shod again from the beginning of the drying.

Studded : apply just one coat of 2 mm in thickness, cross the roller with teeth, and pass with the spatula by touching lightly the material.

Structured : apply just one coat of 2 mm of thickness, and pass spatula by printing material from top to bottom.

Brushed shod : apply a first coat of 1 mm of thickness with the help of the lisseuse, and use the brush to structure the material. After complete drying, shod and apply again a second fine coat with the help of the lisseuse to fill streaks and shod from the beginning of the drying.

PACKAGING AND STORAGE :

MANHATTAN 's Kit Packaging : Liquide part binder : 10 Liters container Powder part : 15 kg bucket

For 10 m² : 1 liter of 740 Imprim 9 kg MANHATTAN 's powder 6 liters MANHATTAN binder